

MIL-STD-188-181
18 SEPTEMBER 1992

MILITARY STANDARD

INTEROPERABILITY STANDARD

FOR

DEDICATED 5-kHz and 25-kHz UHF
SATELLITE COMMUNICATIONS CHANNELS



DISTRIBUTION STATEMENT A. Approval for public release; distribution is unlimited.

(This page intentionally left blank.)

MIL-STD-188-181

FOREWORD

1. Originally, military standard -188 (MIL-STD-188) covered technical standards for tactical and long-haul communications. It later evolved through revisions (MIL-STD-188A, MIL-STD-188B) into a document applicable to tactical communications only (MIL-STD-188C).
2. The Defense Communications Agency (DCA), now the Defense Information Systems Agency (DISA), published DCA circulars (DCAC). These DCACs promulgated standards and engineering criteria that apply to the long-haul Defense Communications System (DCS) and to technical support of the National Military Command System (NMCS).
3. As a result of a Joint Chiefs of Staff (JCS) action, standards for all military communications are now being published in a MIL-STD-188 series. The MIL-STD-188 series is subdivided into a MIL-STD-188-100 series, which covers common standards for tactical and long-haul communications; a MIL-STD-188-200 series, which covers standards for tactical communications only; and a MIL-STD-188-300 series, which covers standards for long-haul communications only. Ultimately, the -200 and -300 series will be absorbed into the -100 series.
4. This MIL-STD was prepared to comply with Joint Staff direction regarding development of a new standard that defines all technical characteristics essential for interoperability and performance of satellite communications (SATCOM) terminals that use dedicated 5-kHz and 25-kHz ultra high frequency (UHF) SATCOM transponder channels. This standard defines mandatory system parameters for planning, engineering, procuring, and using UHF SATCOM terminals in joint operations.
5. This standard is approved and will be used by the Office of the Secretary of Defense, the military departments, the JCS, the unified and specified commands, DoD agencies, and DoD field activities to ensure interoperability and compatibility in accordance with DoD Instruction 5000.2, 23 February 1991.
6. Beneficial comments (recommendations, additions, deletions) and any pertinent data that may be of use in improving this MIL-STD should be addressed to:

Director
Joint Interoperability and Engineering Organization
ATTN: TBBA
Fort Monmouth, New Jersey 07703-5613

by using the standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

(This page intentionally left blank.)

MIL-STD-188-181

CONTENTS

<u>PARAGRAPH</u>		<u>PAGE</u>
1.	SCOPE	1
1.1	Purpose	1
1.2	Scope	1
1.3	Application guidance	1
2.	APPLICABLE DOCUMENTS	3
2.1	Government documents	3
2.1.1	Specifications, standards, and handbooks	3
2.1.2	Other Government documents, drawings, and publications	3
2.2	Non-Government documents	4
2.3	Order of precedence	4
3.	DEFINITIONS	5
3.1	Definitions of terms	5
3.2	Abbreviations and acronyms	7
4.	GENERAL REQUIREMENTS	11
4.1	Communications system characteristics	11
4.2	General waveform structure	11
4.2.1	Operating modes	11
4.2.2	Synchronization	12
4.2.3	Communications security waveform	12
4.2.4	Satellite interface	12
5.	DETAILED REQUIREMENTS	13
5.1	Narrowband mode	13
5.1.1	Transmit	13
5.1.1.1	Effective isotropically radiated power	13
5.1.1.2	Effective isotropically radiated power accuracy	13
5.1.1.3	Transmitter turn-on time	13
5.1.1.4	Adjacent channel emissions	13
5.1.1.4.1	Carrier level less than +18 dBW	13
5.1.1.4.2	Carrier level greater than or equal to +18 dBW	13
5.1.1.5	Tuning	14
5.1.2	Receive	14
5.1.2.1	Susceptibility to adjacent channel interference	14
5.1.2.2	Tuning	14
5.1.2.3	Bit error ratio	14
5.1.3	Modulation	15
5.1.4	Acquisition	15

5.1.4.1	Preamble generation	15
5.1.4.2	Receiver synchronization	15
5.1.4.3	Frequency uncertainty	15
5.1.4.4	Probability of acquisition	15

MIL-STD-188-181

CONTENTS

<u>PARAGRAPH</u>		<u>PAGE</u>
5.1.4.5	Maintaining bit synchronization	15
5.1.4.6	Receive timing stability	15
5.1.5	Frequency generation	15
5.1.6	Voice digitizer	18
5.1.7	Communications security	18
5.1.7.1	Voice	18
5.1.7.2	Data	18
5.1.8	Differential encoding	18
5.2	Wideband mode	20
5.2.1	Transmit	20
5.2.1.1	Effective isotropically radiated power	20
5.2.1.2	Effective isotropically radiated power accuracy	20
5.2.1.3	Transmitter turn-on time	20
5.2.1.4	Adjacent channel emissions	20
5.2.1.5	Tuning	20
5.2.2	Receive	22
5.2.2.1	Susceptibility to adjacent channel interference	22
5.2.2.2	Tuning	22
5.2.2.3	Bit error ratio	22
5.2.3	Modulation	23
5.2.3.1	Deviation	23
5.2.3.2	Input data signal sense	23
5.2.3.3	Frequency-shift keying mark/space convention	23
5.2.4	Acquisition	23
5.2.4.1	Preamble generation	23
5.2.4.2	Receiver synchronization	23
5.2.4.3	Frequency uncertainty	23
5.2.4.4	Probability of acquisition	23
5.2.4.5	Maintaining bit synchronization	23
5.2.4.6	Receive timing stability	23
5.2.5	Frequency generation	25
5.2.6	Voice digitizer	25
5.2.7	Communications security	25
5.2.7.1	Voice	25
5.2.7.2	Data	25
5.2.8	Differential encoding	25
6.	NOTES	25

CONTENTS

<u>FIGURE</u>		<u>PAGE</u>
1A	Proposed synchronization method, for BPSK/SBPSK, narrowband mode	16
1B	Proposed synchronization method for OQPSK/SOQPSK, narrowband mode	17
2	UHF SATCOM terminal, narrowband mode	19
3	Proposed synchronization method, wideband mode	24
4	UHF SATCOM terminal, wideband mode	26

<u>TABLE</u>		<u>PAGE</u>
I	Interoperability data rates	11
II	Allowable adjacent channel emissions, narrowband	13
III	Susceptibility to adjacent channel interference, narrowband mode	14
IV	Allowable adjacent channel emissions, wideband	21
V	Modulation types and susceptibility to adjacent channel interference, wideband mode	22

APPENDIX A	OVERVIEW OF SHAPED BINARY PHASE-SHIFT KEYING MODULATION	29
APPENDIX B	METHOD OF IMPROVING THE (G/T) OF EXISTING ULTRA HIGH FREQUENCY TERMINALS	33
APPENDIX C	OVERVIEW OF LINK CALCULATIONS	37
APPENDIX D	FREQUENCY PLANS	43

(This page intentionally left blank.)