



TEXAS LITHIUM GREASE MP 3

TEXAS LITHIUM GREASE MP 3 is advanced grease with multi-function additives and excellent anti-corrosion agent.

TEXAS LITHIUM GREASE MP 3 is suitable for using under heavy-loading or shock-loading conditions commonly found in automotive, construction, mining or marine industrials with wide range of applications. It provides excellent anti-rust and anti-corrosion properties and dramatically reduces wear under high loading or shock loading. In addition, it offers easy pump ability and is suitable for use in centralized systems. Moreover, it resists water washout and provides extended life in wet environment.

TYPICAL CHARACTERISTICS

Property	Test Method	TEXAS LITHIUM GREASE MP 3
Appearance	Visual	Amber (Yellowish-brown)
Penetration @ 25 °C, 150g (1/10mm)	ASTM D217	231
Dropping Point °C	ASTM 2265	192
Oil Separation @ 100 °C, 24hrs (wt%)	ASTM D1742	0.1
Copper Corrosion @ 100 °C, 24hrs	JISK 2220	Pass

Note: Always consult your owner's manual regarding the viscosity grade and performance classification needed.

Texas Petrochemical reserves the right to modify or change this product with the purpose of improving its performance characteristics.

龍騰

DESEGNO MARKETING

SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

新加坡龍騰企業

特馳中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M
Tel : (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegno marketing@yahoo.com.sg