



## TEXAS LITHIUM GREASE EP 3

TEXAS LITHIUM GREASE EP 3 is premium lithium complex, extreme pressure, high-temperature grease.

TEXAS LITHIUM GREASE EP 3 is suitable for high temperature, high load, shock load and vibration applications in variety of automotive, industrial, construction, mining and marine applications. It is suitable for a wide range of bearing speed extra protection against rust and corrosion. In addition, it reduces wear under heavy or shock load and vibrations offering excellent resistance to water washout and contamination. Furthermore, it provides extended life in wet environments.

### TYPICAL CHARACTERISTICS

Property	Test Method	TEXAS LITHIUM GREASE EP 3
Appearance	Visual	Amber (Yellowish-brown)
Penetration @ 25 °C, 150g (1/10mm)	ASTM D217	225
Dropping Point °C	ASTM 2265	193
Oil Separation @ 100 °C, 24hrs (wt%)	ASTM D1742	0.15
Copper Corrosion @ 100 °C, 24hrs	JISK 2220	Pass
4 Ball Well Load, wt%	ASTM D2596	250

Note: Always consult your owner's manual regarding the viscosity grade and performance classification needed.

Texas Petrochemical reserves the right to modify or change this product with the purpose of improving its performance characteristics.

龍騰

**DESEGNO MARKETING**

SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

新加坡龍騰企業

特馳中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M  
Tel : (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegno marketing@yahoo.com.sg