



TEXAS HYPER HS HYDRAULIC OIL

TEXAS HYPER HS SERIES is a range of high quality anti-wear hydraulic oils specially developed for use in all types of hydraulic systems and equipments. The oil are formulated from selected paraffin base stocks treated with anti-rust, anti-oxidant and anti-wear additives.

TEXAS HYPER HS SERIES 是系列的高质量的防磨损液压油，特别适用于液压系统和设备。本油是由加有防腐，防氧化，防磨损的添加剂的精选蜡加工而成的。

TEXAS HYPER HS SERIES has good demulsibility, thermal stability and anti-foam properties that provide a high degree of equipment protection. It also combines with good filterability and low pour points to allow operation under adverse conditions.

TEXAS HYPER HS SERIES 具有良好的防乳化性，热稳定性和防泡沫性，为机械设备提供高质量的保护。良好的渗透性和低倾点的特性使得在恶劣环境下的操作顺利进行。

TYPICAL CHARACTERISTICS

特性

Test Method 试验方法	32	46	68	100
	Result 结果			
Appearance 外观	B&C	B&C	B&C	B&C
Density @15°C, kg/L 密度 @ 15°C, kg/L	0.875	0.880	0.885	0.890
Viscosity @40°C, cSt 运动 粘度 @40°C, cSt	32	46	68	102
Viscosity @100°C, cSt 运动 粘度 @100°C, cSt	5.3	6.8	8.6	11.4
Viscosity Index 粘度指数	106	104	98	95
Flash Point, °C 闪点, °C	220	230	230	235
Pour Point, °C 倾点, °C	-30	-27	-24	-22

Performance Standards

标准

- * DIN 51524 Part 2
- * AFNOR NFE 48-603
- * DENISON HF-2
- * CINCINNATI MILACRON P-68, P69, P70

Texas Petrochemical reserves the right to modify or change this product with the purpose of improving its performance characteristics.

龍騰

DESEGNO MARKETING

SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

新加坡龍騰企業

特驰中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M
Tel : (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegno marketing@yahoo.com.sg