



## TEXAS HYPER AW HYDRAULIC OIL

**TEXAS HYPER AW SERIES** is a range of high quality anti-wear hydraulic oils specially developed for use in all types of hydraulic systems and equipments. The oils are formulated from selected paraffin base stocks treated with antirust, antioxidant and anti-wear additives.

**TEXAS HYPER AW SERIES** 是系列的高质量的液压油，特别适用于液压系统和设备。本油是由加有防腐，抗氧化，防磨损的添加剂的精选蜡加工而成的。

**TEXAS HYPER AW SERIES** has good demulsibility, thermal stability and anti-foam properties that provides a high degree of equipment protection. It also combines with good filterability and low pour points to allow operation under adverse conditions.

**TEXAS HYPER AW SERIES** 具有良好的防乳化性，热稳定性和防泡沫性，为机械设备提供高质量的保护。良好的渗透性和低倾点的特性使得在恶劣环境下的操作顺利进行。

### TYPICAL CHARACTERISTICS      特性

	32	46	68	100
Test Method 试验方法	Result 结果			
Appearance 外观	B&C	B&C	B&C	B&C
Density @15°C, kg/L 密度 @ 15°C, kg/L	0.875	0.880	0.885	0.890
Viscosity @40°C, cSt 运动 粘度 @40°C, cSt	32	46	68	102
Viscosity @100°C, cSt 运动 粘度 @100°C, cSt	5.3	6.7	8.4	11.4
Viscosity Index 粘度指数	106	104	98	95
Flash Point, °C 闪点, °C	218	227	227	230
Pour Point, °C 倾点, °C	-30	-27	-24	-20

### Performance Standards      标准

- DIN 51524 Part 2
- AFRNOR NFE 48-603
- DENISON HF-2
- CINCINNATI MILACRON P-68, P69, P70

Texas Petrolchemical reserves the right to modify or change this product with the purpose of improving its performance characteristics.



**DESEGNO MARKETING**  
SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

**新加坡龍騰企業**  
特驰中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M  
Tel : (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegno marketing@yahoo.com.sg