



TEXAS TEXMARINE 80

TEXAS TEXMARINE 80 is a high performance oil for the diesel engines fitted for marine applications (fishing boats, inland transport), industrial applications (power generation, offshore well drilling rig) and railroads.

TEXAS TEXMARINE 80 是一种性能优越的机油，用于安装在下陆列设备上的柴油发动机的润滑：船只（渔船及内船只）工业设备（发电厂，近海钻井用的钻机）铁路机车。

PROPERTIES 性质

- Monograde 单级黏度
- Very high dispersion level. 出色的高分散性
- Excellent resistance to the oxidation degradation. 出色的抗氧化降解性能
- Good TBN retention. 良好的中和值保持能力
- Exceptional detergency level. 超凡的清洁性
- Anti-corrosion, anti-rust and anti-wear properties. 兼备耐腐蚀, 防锈及磨损性能
- Very good anti-foam properties. 优秀的抗起泡性

TYPICAL CHARACTERISTICS 特性

Property 性质	Test Method 试验方法	TEXAS TEXMARINE 80	
		SAE 30	SAE 40
Density @15°C, kg/L 密度 @ 15°C, kg/L	ASTM D4052	0.895	0.898
Viscosity @40°C, cSt 运动粘度 @40°C, cSt	ASTM D445	109	143
Viscosity @100°C, cSt 运动粘度 @100°C, cSt	ASTM D445	11.8	14.2
Viscosity Index 粘度指数	ASTM D2270	99	99
Flash Point, °C 闪点, °C	ASTM D92	210	220
Pour Point, °C 倾点, °C	ASTM D97	-15	-10
TBN 中和值	ASTM D2896	8	8

Performance Standards 标准

- API CF

Texas Petrochemical reserves the right to modify or change this product with the purpose of improving its performance characteristics.



DESEGNO MARKETING

SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

新加坡龍騰企業

特驰中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M
Tel : (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegno marketing@yahoo.com.sg