



TEXAS TEXMARINE 300

TEXAS TEXMARINE 300 are suitable for highly rated turbocharged. Medium speed engines burning heavy fuel oil with high sulphur content

TEXAS TEXMARINE 300 适用于烧高含量重燃油的高级涡轮增压中柴油机。 具体为：

- marine engines 船用发动机
- industrial engines (power station) 工业发动机 (发电站)

PROPERTIES 性质

- Single grade. 单级黏度
- Very high level of alkalinity. 突出的高碱度
- Exceptionally high level of dispersion and detergency. 超凡的分散性清洁性
- Excellent resistance to oxidation at high temperature. 高温下出色的抗氧化性
- High load carrying capacity. 高承载能力
- Excellent anti-wear, anti-rust and anti-foaming properties. 出色的抗磨损，防锈及抗起泡性能

TYPICAL CHARACTERISTICS 特性

Property 性质	Test Method 试验方法	TEXAS TEXMARINE 300	
		SAE 30	SAE 40
Density @15°C, kg/L 密度 @ 15°C, kg/L	ASTM D4052	0.910	0.915
Viscosity @40°C, cSt 运动粘度 @40°C, cSt	ASTM D445	108	143
Viscosity @100°C, cSt 运动粘度 @100°C, cSt	ASTM D445	12.0	14.3
Viscosity Index 粘度指数	ASTM D2270	100	100
Flash Point, °C 闪点, °C	ASTM D92	225	230
Pour Point, °C 倾点, °C	ASTM D97	-15	-10
TBN 中和值	ASTM D2896	30	30

Performance Standards 标准

- API CF

Texas Petrochemical reserves the right to modify or change this product with the purpose of improving its performance characteristics.



DESEGNO MARKETING

SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

新加坡龍騰企業

特驰中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M
Tel : (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegnmarketing@yahoo.com.sg