



TEXAS TEXMARINE 800

TEXAS TEXMARINE 800 is suitable for cylinder lubrication of engines burning high and very high sulphur content residual fuel oils.

TEXAS TEXMARINE 800 适用于以高含硫及特高含硫的渣油作为燃料的柴油机汽缸润滑。

PROPERTIES 性质

- Very high level of detergency and dispersion. 出色的清洁机分散性
- High anti-wear properties. 高抗磨损能力
- Anti-corrosive and anti-rust properties. 兼备防腐蚀及防锈性能
- Very high neutralizing power on acidic product formed during combustion: TBN of 80mg KOH/g. 对燃料燃烧过程中产生的酸性物质具有超强的中和能力，中和值不低于80mg KOH/g
- High viscosity of SAE 50 具有 SAE 50 的高黏度

TYPICAL CHARACTERISTICS 特性

Property 性质	Test Method 试验方法	TEXAS TEXMARINE 400	
		SAE 40	SAE 50
Density @15°C, kg/L 密度 @ 15°C, kg/L	ASTM D4052	0.930	0.935
Viscosity @40°C, cSt 运动粘度 @40°C, cSt	ASTM D445	160	220
Viscosity @100°C, cSt 运动粘度 @100°C, cSt	ASTM D445	15.7	19.5
Viscosity Index 粘度指数	ASTM D2270	100	100
Flash Point, °C 闪点, °C	ASTM D92	220	230
Pour Point, °C 倾点, °C	ASTM D97	-10	-10
TBN 中和值	ASTM D2896	80	80

Performance Standards 标准

- API CF

Texas Petrolchemical reserves the right to modify or change this product with the purpose of improving its performance characteristics.



DESEGNO MARKETING

SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

新加坡龍騰企業

特驰中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M
Tel : (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegno marketing@yahoo.com.sg