



TEXAS GALAXY POWER PREMIUM ENGINE OIL

MULTI-GRADE OIL GASOLINE & DIESEL ENGINES

USES

- TEXAS GALAXY POWER has been developed to cover the most stringent requirements of both gasoline and diesel engines.
- TEXAS GALAXY POWER is suited to turbocharged engines.
- TEXAS GALAXY POWER can be used in all operating conditions (city, traffic, road, motorways...) whatever the season.
- TEXAS GALAXY POWER is adapted to all vehicles equipped with catalysts and using unleaded fuel.

PROPERTIES

- Meets the new API SJ requirements, guarantee a high and constant quality for the lubricant.
- High Performance multi-grade oil.
- Very high viscosity index in operation.
- Excellent thermal stability.
- Excellent discrepancy and detergency
- Excellent anti-wear properties perfectly protecting the engine.
- Very good anticorrosion, antirust, antifoaming properties.
- Reduces the risk of destructive pre-ignition

用途

- 可同时满足汽油机和柴油机最严格的要求。
- 尤其适用于涡轮增压和多阀门发动机。
- 可在任何季节用于最恶劣的工作条件（快速车道，繁忙的城市道路）。
- 特别适用于装有催化装置并使用无铅汽油的车辆。

特性

- 满足APISJ的要求，确保润滑油长期稳定保持高质量。
- 超级多级粘度机油。
- 使用中出色的高粘度指数。
- 出色的热稳定。
- 优秀的分散清净性。
- 突出的防磨性能，全面，充分保护发动机。
- 优秀的抗腐蚀，防锈及抗泡性能。
- 减少破坏性提前点火现象的发生。

Texas Galaxy Power	Units	SAE 15W40	SAE20W50
Volumetric mass at 15°C 密度 15°C	Kg/m ³	885	895
Viscosity at 40°C, cSt 运动粘度 40°C, cSt	mm ² /s	173	156
Viscosity at 100°C, cSt 运动粘度 100°C, cSt	mm ² /s	19.6	17
Viscosity index 粘度指数	-	130	117
Flash point Cleveland 闪点 (开口)	°C	229	235
Pour point 倾点	°C	-24	-21

PERFORMANCE STANDARD

API SJ/CF API CF/CD

Texas reserves the right to modify or change this product with the purpose of improving its performance characteristics.



DESEGNO MARKETING
SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

新加坡龍騰企業
特驰中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M
Tel: (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegnomarketing@yahoo.com.sg