



# TEXAS REXTON

## PREMIUM QUALITY DIESEL ENGINE OIL

### MONOGRADE OIL FOR DIESEL ENGINES

#### USES

- TEXAS REXTON is suitable to all turbocharged or normally aspirated engines which equip civil works machines and trucks, fishing boats.
- Gear boxes, torque converters, hydraulic systems when the manufacturer requires an engine oil with an appropriate grade for these applications.

#### PROPERTIES

- Monograde.
- Very high viscosity.
- Exceptional detergency level.
- Very high dispersancy level.
- High stability in operation.
- Excellent anti-wear and anticorrosion properties.
- Very good antioxidant, antirust and anti-foaming properties.

#### 用途

- 适用于所有安装在工程机、卡车和渔船上的涡轮增压或自然进气的柴油发动机。
- 当制造厂商要求使用适当级别润滑油的情况下，使用于齿轮箱，扭矩转换器，液压系统。

#### 特性

- 单级粘度。
- 高粘度指数。
- 突出的高清洁性。
- 上佳的分散性。
- 工作中优越的粘度稳定性。
- 卓越的抗磨损及抗腐蚀性能。
- 优越的抗氧化、防锈及抗泡性能。

Texas Rexton	Units	SAE 40	SAE 50
Volumetric mass at 15°C 密度 15°C	Kg/m <sup>3</sup>	892	898
Viscosity at 40°C, cSt 运动粘度 40°C, cSt	mm <sup>2</sup> /s	147.2	223.3
Viscosity at 100°C, cSt 运动粘度 100°C, cSt	mm <sup>2</sup> /s	14.5	19.2
Viscosity index 粘度指数	-	97	96
Flash point Cleveland 闪点 (开口)	°C	242	250
Pour point 倾点	°C	-12	-12

#### PERFORMANCE STANDARD

API CF/CF2  
API SF  
FZG  
JASO MA

Texas reserves the right to modify or change this product with the purpose of improving its performance characteristics.

龍騰

**DESEGNO MARKETING**  
SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

**新加坡龍騰企業**  
特驰中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M  
Tel: (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegno marketing@yahoo.com.sg