



## TEXAS HYFLOW HIGH QUALITY HYDRAULIC TRANSMISSION OIL

### USES

- TEXAS HYFLOW is a superior quality oils recommended for the use in circulation systems and in hydraulic circuits.
- TEXAS HYFLOW is suitable for all hydrostatic systems operating under high pressure and high temperature.

### PROPERTIES

- High viscosity index.
- No shear.
- Excellent thermal stability and exceptional resistance to oxidation.
- Very good hydrolytic stability, excellent demulsibility and low pour point.

### 用途

- TEXAS HYFLOW 是一种性能优越的机油，并适用于任何工作条件，精密机器。
- 适用于所有在高压和高温条件下工作的静液压系统。

### 特性

- 高粘度指数。
- 无剪切要求。
- 优越的热稳定性及突出的抗氧化性。
- 优秀的液压稳定性及出色的抗乳化性并保有特低倾点。

Texas Hyflow Series		Units	32	46	68	100
Volumetric mass at 15°C	密度 15°C	Kg/m <sup>3</sup>	870	874	883	887
Viscosity at 40°C, cSt	运动粘度 40°C, cSt	Mm <sup>2</sup> /s	32	45	67	100
Viscosity at 100°C, cSt	运动粘度 100°C, cSt	Mm <sup>2</sup> /s	5.4	6.8	8.6	11.4
Viscosity index	粘度指数	-	106	100	98	96
Flash point Cleveland	闪点 (开口)	°C	215min	220min	220min	220min
Pour point	倾点	°C	-15	-15	-15	-15

### PERFORMANCE STANDARDS

ISO-L-HL      DIN 51524 part 1 HL

Texas reserves the right to modify or change this product with the purpose of improving its performance characteristics.

龍騰

**DESEGNO MARKETING**  
SOLE AGENT PEOPLE'S REPUBLIC OF CHINA

**新加坡龍騰企業**  
特驰中国一级代理商

No. 14 Shaw Road #04-01 BTC Building Singapore 367952 ROC No. 52939077M  
Tel: (65) 6 288 3602 Fax: (65) 6 288 3697 Email: desegno marketing@yahoo.com.sg