

### **VIVERGY CO.,LTD**

### The High-Tech Filter and Mixer

### **Vivergy Side Entry Mixer - FX Series Standard Features**



**VIVERGY** Side Entry Mixers are designed for solids suspension and mixing. **VIVERGY** proven side Entry design assures you of a machine that will perform to the required task and give many years of reliable service. The following is some major advantages in using a **VIVERGY** Side Entry Mixer:

- Fast and Easy Seal Change while tank is full
- No Need to remove V-Belts to access seal
- V-Belts or Tooth Belt Drives available
- Fully enclosed and sealed bearings with a fatigue
  life of more than 100,000 hours
- No in Tank Bearings
- Choice of Wetted parts materials
- Double mechanical Seals with lubricators and Explosion proof motors available
- Variable Stand configuration to suit the terrain around the tank and Drives are Cycloid.
  Drive selection of your choice can be applied
- Side Doors can be provided for ease of cleaning and inspection



Contact: Vivergy Co.,Ltd.

22/1, Soi Punna Vithi 29, Sukhumvit 101 Rd., Bangchak, Phrakhanong, Bangkok 10260 Thailand Tel: (+662) 730 5702, Fax: (+662) 730 5701, E-mail: <a href="mailto:floculation@yahoo.com">floculation@yahoo.com</a>, <a href="https://www.vivergy.net">www.vivergy.net</a>





## **VIVERGY CO.,LTD**

### The High-Tech Filter and Mixer

# **Applications**


Food Industry	Cocoa Butter Blending and storage
Edible Oil Industry	Crude Oil Storage, Bleaching, Winterization in horizontal tanks
Transportation Industry	Transportation Industry
Petrochemical Storage	Crude Oil Storage
Ceramic Industry	Slip Storage

## **Special Options**


- Leak Detector Sensor Alarm
- Storage tank low level cut off

- Lock off Unit





Seal Isolation Unit with Viton Seating and 4 Point clamp Plate



Seal Isolation Unit with Metal on Metal Seating and Single Point Pivot Fork Engagement





# **VIVERGY CO.,LTD**

## The High-Tech Filter and Mixer

# **General Specifications**

Motor	IEC Standard Frames Reputable Brands such as ABB or Siemens
Motor Protection	IP 55 TEF ( EXE & EXD Available )
Mechanical Seal Type	Single or Double Acting
Mechanical Seal Rating	Vacuum to 12 Bar
Belt Grip	Vee Belt or Tooth Belts available
Seal Isolation device Rating	3 Bar, 6 Bar, 12 Bar and 25 Bar available
Impeller Fixings	Bolted Impellers with keeper plates and slots
Seal Isolation Device Housing	SUS316 housing with Viton Seat or Metal on Metal Sealing
Pulley Connection	Taper Lock
Drip Collection	1-10 L
Bearings Make	Bearings SKF or NTN
Bearing Type	Spherical Roller Bearings Fully Sealed
Flange	ANSI, DIN or JS Flanges
Speed Accuracy	± 5%



22/1, Soi Punna Vithi 29, Sukhumvit 101 Rd., Bangchak, Phrakhanong, Bangkok 10260 Thailand Tel: (+662) 730 5702, Fax: (+662) 730 5701, E-mail: <a href="mailto:floculation@yahoo.com">floculation@yahoo.com</a>, <a href="mailto:www.vivergy.net">www.vivergy.net</a>

