

SPESIFIKASI TEKNIK / TECHNICAL SPECIFICATION

Kapasitas <i>Capacity</i>	Arus beban Nol <i>Exciting Current Io</i>	Impedansi <i>Impedance Zsc</i>	Rugi - 2 Besi <i>No load losses</i>	Rugi- 2 Tembaga <i>Load losses</i>	Rugi - 2 Total <i>Total losses</i>	Efisiensi pada 75°C Faktor daya : 1,0 <i>Efficiency</i>				Pengaturan pada beban penh <i>Voltage Regulation</i>		Dimensi / Dimension toleransi 5%			Volume oil	Berat (Weight)
						Beban Load				Faktor daya Power Factor		A Panjang (length)	B Lebar (Width)	C Tinggi (Height)		
kVA	%	%	Watt	Watt	Watt	100%	75%	50%	25%	1.0	0.8	MM	MM	MM	Liter	Kg
25	3,0	4,0	120	680	800	96,90	97,39	97,73	97,47	2.76	3.94	1030	565	1105	140	480
50	2,8	4,0	190	1100	1290	97,48	97,89	98,17	97,97	2.26	3.77	1100	625	1145	160	500
100	2,5	4,0	320	1750	2070	97,97	98,29	98,51	98,31	1.81	3.57	1290	760	1190	210	850
160	2,3	4,0	460	2350	2810	98,27	98,54	98,71	98,51	1.54	3.43	1290	780	1275	250	1050
200	2,2	4,0	550	2850	3400	98,33	98,58	98,75	98,56	1.49	3.41	1290	780	1290	250	1050
250	2,1	4,0	650	3250	3900	98,46	98,70	98,84	98,65	1.37	3.33	1390	780	1370	350	1370
315	2,0	4,0	770	3900	4670	98,54	98,76	98,90	98,73	1.31	3.30	1440	755	1480	400	1550
400	1,9	4,0	930	4600	5530	98,64	98,48	98,97	98,80	1.22	3.25	1440	755	1510	440	1800
500	1,9	4,0	1100	5500	6600	98,70	98,89	99,02	98,86	1.17	3.22	1540	825	1620	560	1930
630	1,8	4,0	1300	6500	7800	98,78	98,96	99,08	98,93	1.11	3.17	1570	865	1660	590	2180
800	2,5	4,5	1950	10200	12150	98,50	98,73	98,89	98,72	1.37	3.65	1690	975	1695	725	2900
1000	2,4	5,0	2300	12100	14400	98,58	98,80	98,95	98,79	1.33	3.93	1840	1100	1720	815	3100
1250	2,7	5,5	2700	15000	17700	98,60	83,83	98,98	98,85	1.34	4.25	1930	1125	1760	1020	3550
1600	2,0	6,0	3300	18100	21400	98,68	98,89	99,03	98,80	1.30	4.52	2030	1205	1805	1180	4340
2000	1,9	6,0	3900	21000	24900	98,77	98,96	99,09	98,97	1.22	4.41	1950	1890	1965	1630	5250
2500	1,8	7,0	4500	28000	32500	98,72	98,93	99,09	99,01	1.36	5.16	2300	2020	2075	1680	5700