

XLV



The XLV by United Trailers is perfect for the person who wants a quality-built trailer at an unbeatable value. The XLV is designed to help with all of your most basic hauling needs. It comes loaded with several impressive features such as a 24" V-Nose, .030 aluminum exterior, 3/8" plywood interior walls, and 3" rub rail. When you want exceptional value, look no further than the XLV.

Trailers shown may feature optional equipment available at an additional charge.



Your Authorized United Trailers Dealer:

BUILT FOR THE LONG HAUL

SPECIFICATIONS

XLV

MODEL		XLV-58SA3	XLV-510SA3	XLV-610SA3	XLV-612SA3	XLV-612TA35	XLV-614SA3	XLV-614TA35	XLV-712TA35	XLV-714TA35	XLV-716TA35
Body:	Length	10' 0"	12' 0"	12' 0"	14' 0"	14' 0"	16' 0"	16' 0"	14' 0"	16' 0"	18' 0"
	Width	5' 0"	5' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	7' 0"	7' 0"	7' 0"
Overall:	Length	11' 6"	13' 6"	13' 6"	15' 6"	15' 6"	17' 6"	17' 6"	15' 6"	17' 6"	19' 6"
	Width	6' 8"	6' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	8' 6"	8' 6"	8' 6"
	Height	6' 7"	6' 7"	7' 7"	7' 7"	7' 8"	7' 7"	7' 8"	7' 10"	7' 10"	7' 10"
Interior:	Length	9' 7-1/2"	11' 7-1/2"	11' 7-1/2"	13' 7-1/2"	13' 7-1/2"	15' 7-1/2"	15' 7-1/2"	13' 7-1/2"	15' 7-1/2"	17' 7-1/2"
	Width	4' 8"	4' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	6' 8"	6' 8"	6' 8"
	Height	4' 10-1/2"	4' 10-1/2"	5' 10-1/2"	5' 10-1/2"	5' 10-1/2"	5' 10-1/2"	5' 10-1/2"	6' 0"	6' 0"	6' 0"
Rear Door Opening:	Width	52"	52"	64"	64"	64"	64"	64"	76"	76"	76"
	Height	55"	55"	67"	67"	67"	67"	67"	69"	69"	69"
Platform Height		17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	18-3/4"	18-3/4"	18-3/4"
Axles		Single	Single	Single	Single	Tandem	Single	Tandem	Tandem	Tandem	Tandem
Axle Type		4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop
Suspension		Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring
Tire Size		ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Load Range		C	C	C	C	C	C	C	C	C	C
Wheel Bolt Pattern		5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5
Hitch Ball Size		2"	2"	2"	2"	2-5/16"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch to Top of Ball		16"	16"	16"	16"	17"	16"	17"	17"	17"	17"
Hitch Weight (% of Curb Weight)		10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%
Avg Curb Weight (lbs.)		955	1065	1245	1370	1765	1480	1955	1960	2105	2270
GVWR (lbs.)		2,990	2,990	2,990	2,990	7,000	2,990	7,000	7,000	7,000	7,000
GAWR (lbs.)		3,000	3,000	3,000	3,000	7,000	3,000	7,000	7,000	7,000	7,000
Avg. Payload Capacity		2035	1925	1745	1620	5235	1510	5045	5040	4895	4730

Specifications and features subject to change without notice.

STANDARD FEATURES

- Steel Unibody Construction
- Protective Undercoating
- 24" V-Nose
- Dexter 4" Drop Spring Axles w/ E/Z Lube Hubs
- 15" Radial Tires w/ White Mod Steel Wheels
- 2" Coupler with Jack on Single Axle
- 2-5/16" Coupler with Jack on Tandem Axle
- DOT Safety Chains
- 4-Way Trailer Plug on Trailers w/o Brakes
- 7-Way Trailer Plug on Trailers w/ Brakes
- 3" Tube Main Frame on Single Axle 5 & 6 Wide
- 4" Tube Frame on all 7 Wide and Tandem Axle
- 24" On-Center Roof Tubes
- 24" On-Center Vertical Hat Posts
- 24" On-Center Crossmembers
- Clear LED Surface Mounted Tail & Clearance Lights
- 3/8" Plywood Interior Walls
- 3/4" Engineered Wood Flooring
- (1) 12-Volt LED Dome Light w/ Switch
- .030 Smooth Aluminum Exterior (13 Colors Available)
- Screwed Exterior
- 32" x 64" Blank RV Door (6' and 7' wide only)
- Smooth Aluminum Fenders
- 24" x .045 Aluminum Tread Plate Stoneguard
- Flow-Thru Sidewall Vents
- Fold Down Stabilizer Jacks
- Double Rear Doors
- 1 Year Limited Warranty

