



SECTION "A-A"

~MATERIALS LIST~		
COMPONENT	SIZE	QUANTITY
SIDES	3/4 PLY, 19.00 x 19.25, CUT AS SHOWN	2
HORIZONTAL BOTTOM RAILS	2" x 4" x 26.00"	2
VERTICALS, LONG	2" x 4" x 16.00"	2
VERTICALS, SHORT	2" x 4" x 5.00"	2
VERTICALS, SHORT	2" x 4" x 5.00"	2
VERTICAL, SINGLE OUTSIDE	2" x 4" x 6.00"	1
BRACE, BACK	3/4 PLY, 8.00" x 7.25"	1
BRACE, BOTTOM	3/4 PLY, 18.25" X 7.25"	1

NOTES:

1. The 2"x4" stock used actually measured out at 1-1/2" x 3-1/2". Plywood was a full 3/4" thick. Adjust dims as required to suit your lumber.
2. Outside/outside dimension of 8.75" is a MAXIMUM dimension; shortening that to 8.50" would ease installation.
3. None of these dimensions are critical, save for the outside/outside dim mentioned above, and the distance from holes to the horizontal member toward the rear.
4. Stand will hold a frame in approximately the same position as the frame on a rolling chassis, but with a bit of clearance between wheels & ground.
5. All assembly was with black woodscrews.

MATERIAL: 3/4 PLYWOOD, 2"x4" STOCK, DRYWALL SCREWS AS REQ'D	TOLERANCES UNLESS OTHERWISE SPECIFIED .XXX=±.015 HOLES=±.003 .XXX=±.005 ANG.=±1°	WORKSTAND
	R. ZMDARS 1-15-2002	