



## PRODUCT DATA SHEET

# MetalCleaner – 200

### Surface Preparation

#### GENERIC TYPE:

A Solvent-Cleaner Blend

#### DESCRIPTION:

**MetalCleaner- 200** is a Surface treating agent for preparing previously coated surfaces for recoating after they have been allowed to cure past recommended recoat times or have been exposed to sunlight for extended periods of time

#### FEATURES:

- A thorough water rinse-off after use will leave a residue-free surface

#### RECOMMENDED USES:

**MetalCleaner-200** is recommended for cleaning **PhenoSany** Tank Linings coatings which have cured past their recommended recoat times and **SanyMastic** (Epoxy Coal Tar) or **EpoSany** (Epoxies) which have been exposed to sunlight for over 36 hours or more.

#### SURFACE PREPARATION:

Wipe the surface thoroughly with clean rags soaked in **MetalCleaner-200**. Renew rag when it becomes contaminated. All surfaces must be wiped.

#### Safety Cautions:

Caution: Avoid prolonged breathing of vapours and skin contact. Use in a well ventilated area. Smoking or the use of electrical equipment that could cause sparks should be prohibited while this product is being applied. Avoid contact with eyes, skin and clothing. Wear gloves and protect face during application. In case of contact with eyes, flush immediately with plenty of water. Get medical attention promptly. If skin contact occurs wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. Wash hands thoroughly before eating or smoking, Should **MetalCleaner-200** be swallowed accidentally, contact physician immediately.

#### Note

Read and follow all caution statements on this product data sheet and on the MSDS for this product. Employ normal workmanlike safety precautions. Hypersensitive persons should wear protective clothing, gloves and use protective cream on face, hands and all exposed areas. Personal protective equipment meeting the requirements of the COSHH regulations should be worn.

#### Ventilation

When used as a tank lining or in enclosed areas, thorough air circulation must be used during and after application until the coating is cured. The ventilation system should be capable of preventing the solvent vapour concentration from reaching the lower explosion limit for the solvents used. In addition to ensuring proper ventilation, appropriate respirators must be used by all application personnel. Appropriate Working in Confined Spaces Regulations should be followed.



FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN. 1/2001

#### SPECIFICATION DATA

• Flammable	Flash Point: + 73 °F ( 23 °C ) ( Pensky-Martens closed Cup )
• Theoretical Coverage :	400 – 800 sq. ft. per gallon. Depends on the surface roughness and contours
• Shelf Life :	24 months when stored at 75 °F ( 24 °C ).
• Storage Conditions:	Store indoors.
Temp.:	4 - 43 °C
Humidity:	0 - 200%



#### Additives & Specialties

#### Contact




For information and Prices, Please Call a SANYCHEM Local Sales Representative.

#### Phones:



+58-212-6313092 | +58-414-3142752 | Fax: +58-212-6312441



Internet:  
[www.sanychem.com](http://www.sanychem.com)  
[sanychem@cantv.net](mailto:sanychem@cantv.net)  
[sales@sanychem.com](mailto:sales@sanychem.com)

January 2001 replaces May 1999

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact **SanyChem** Company to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to **SanyChem** quality control. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of products. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SANYCHEM, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. **SanyChem** and **KoraTex** are registered trademarks of **SanyChem** Company.